

Technical Specifications for Tree Guards

Product Description

Supply of Concrete Tree Guards of VYARA make, comprising:


- UV-resistant colour pigments from Lanxess or approved, in colours as specified by the architect
- Wear-resistant, colour-coordinated aggregates for enhanced surface durability and visual uniformity
- Design as per the images provided below



TG-2
800x800x75mm, ID 500mm



TG-3
950x950x75mm, ID 650mm



TG-4
900x900x100mm, INL 700mm

Technical Parameters

Sr.	Parameters	Minimum Requirements
1.	Tolerance in Size (Length & Breadth)	±2.5 mm
2.	Tolerance in Thickness (mm)	±4 mm
3.	Water Absorption	Average not over 8%

Manufacturing & Quality Assurance

Manufacturing Process:

The paving blocks must be cured in a controlled environment to ensure efflorescence free material.

Vyara Tiles Limited

903-904 Rajhans Montessa, Near Le Meridian, Dumas Road, Surat 395007

Ph: 0261-2471595, 2472444 | E-mail: info@vyaratiles.in | Website: www.vyaratiles.in

Quality Certifications:

The manufacturer must be ISO 9001:2015 certified or have equivalent quality management systems in place to ensure quality product.

Sustainability Requirements:

The product must meet the sustainability criteria and should be certified as a green product (GreenPro) by CII.

Testing Facilities:

The manufacturer must have an in-house laboratory equipped to perform these tests:
Water Absorption | Compressive Strength | Flexural Strength | Abrasion Resistance